

Module	D22-ENC410 (Touch)	D24-ENC410 (Non-Touch)
Photo		
CPU Support	Intel LGA1200 10th Gen. CPU, TDP 65W	Intel LGA1200 10th Gen. CPU, TDP 65W
CPU Support	Intel LGA1200 10th Gen. CPU, TDP 65W	Intel LGA1200 10th Gen. CPU, TDP 65W
Mainboard	H410H6-TI2	H410H6-TI2
Color	Black/White	Black/White
Panel (LED)	21.5", 1920x1080, Full HD. 14-20ms response Time, 1000:1 contrast ratio	21.5", 1920x1080, Full HD. 14-20ms response Time, 1000:1 contrast ratio
Touch	10 points Capacity Touch Screen	NA
WebCam	2M Pixels	2M Pixels

<b>AIO Rear IO</b>	DC-In jack x 1 (19V) HDMI-Out x 1 , D_Sub x 1 USB3.0 Port x 2, USB2.0 port x 2 GiGabit LAN x 1 Earphone-Out x 1 MIC x 1	DC-In jack x 1 (19V) HDMI-Out x 1 , D_Sub x 1 USB3.0 Port x 2, USB2.0 port x 2 GiGabit LAN x 1 Earphone-Out x 1 MIC x 1
<b>AIO Side IO</b>	USB 2.0 x 2, Card Reader, MIC/EarPhone	USB 2.0 x 2, Card Reader, MIC/EarPhone
<b>VESA Mount Holes</b>	75*75mm	75*75mm
<b>Memory DIMM Slot</b>	max. 32GB ,DDR4 SO-DIMM x 2 2666MHz	max. 32GB ,DDR4 SO-DIMM x 2 2666MHz
<b>WiFi / BT Slot</b>	m.2 2230 with Intel 3165 card	m.2 2230 with Intel 3165 card
<b>Storage Device</b>	Support 1 x 2.5" hard disk Support 1 x m.2 2280 SSD (SATA/PCI-E)	Support 1 x 2.5" hard disk Support 1 x m.2 2280 SSD (SATA/PCI-E)
<b>ODD Driver (Option )</b>	1	1
<b>Speaker Module</b>	3W x 2 Speaker	3W x 2 Speaker
<b>Power Supply + Power Cord</b>	120W/19V/6.32A , US power cord	120W/19V/6.32A , US power cord
<b>Stand</b>	L type stand	L type stand
<b>Accessories</b>	Manual, QIG, Driver DVD	Manual, QIG, Driver DVD
<b>Packing</b>	Standard brown box packing, EPE sponge and labels 20'/40': 320 pcs / 640 pcs	Standard brown box packing, EPE sponge and labels 20'/40': 320 pcs / 640 pcs

**Dimension**

Net: (W)490x (D)180x (H)380,  
7Kgs(w/ stand)  
Gross: (W)585x (D)180x  
(H)450mm, 7.8Kgs

Net: (W)490x (D)180x (H)380, 7Kgs(w/ stand)  
Gross: (W)585x (D)180x (H)450mm, 7.8Kgs